

Web Images Maps News Shopping Gmail more ▾

Sign in



drop doorbell buffer register queue

Search

Advanced Search
Preferences

Web

Results 1 - 10 of about 1,200 for drop doorbell buffer register queue. (0.36 seconds)

Tip: Save time by hitting the return key instead of clicking on "search"

1.22001/10/02 23:05:14 * linux/include/linux/cyclades.h * * This ...
 struct CUSTOM_REG { uulong foga_id; /* FPGA Identification Register */ uulong Tx
 buffer */ #define C_CM_Q_ENABLE 0x58 /* enables queue access from the ...
 cvs.sourceforge.jp/cgi-bin/viewcvs.cgi/linux-h8/uClinux-2.0.x/include/linux/cyclades.h?
 rev=1.1.1.1 - 26k - Cached - Similar pages

Re: [ofa-general] post_recv question | KernelTrap

36 posts - Last post: Feb 21, 2006

When you post to a receive queue, the buffer does not belong the ... post_recv code rings
 a doorbell (write to adapter mem or register) t3: ...

<https://kerneltrap.org/mailarchive/openfabrics-general/2006/2/21/939994/thread> - 102k -
 Cached - Similar pages

Re: [ofa-general] post_recv question | KernelTrap

... hw work queue t2: post_recv code rings a doorbell (write to adapter mem or register) t3:
 post_recv returns t4: &t;app assumes the buffer is ready&t; ...

<https://kerneltrap.org/mailarchive/openfabrics-general/2006/2/21/939554/thread> - 102k -
 Cached - Similar pages

More results from <https://kerneltrap.org> ..

Source Code, Sample Code or Example Code For writel

sa_writel(dev, Mailbox4, 0); /* * Clear the synch command doorbell to start on a
 vb.queue); q->curr = buf; DEB_INT(("next buffer: buf:%p, prev:%p, ...
www.codase.com/search/call?name=writel - 67k - Cached - Similar pages

[PDF] InfiniBand Support in Xen Virtual Machine Environment

File Format: PDF/Adobe Acrobat - View as HTML

HCA and register a callback handler with CQ. Completion queue can also be accessed
 through buffer and ringing the doorbell to notify the ...

<ftp://ftp.cse.ohio-state.edu/pub/tech-report/2005/TR63.pdf> - Similar pages

BSDCon '03 — Technical Paper

In addition to context switch overhead, the memory buffer used to stage data to and from ...
 unit doorbell or queue pointer register is written is critical. ...

www.usenix.org/events/bsdcon03/tech/full_papers/thorpe/thorpe_hmtl/index.html - 146k -
 Cached - Similar pages

GIT e4f775874f071120204c58a21eafe132ca5f2396 master.kernel.org ...

+ /* + /* disable the RAM Buffer receive queue */ + sky2_write8(hw, RB_ADDR(rxqaddr
 [port], RB_CTRL), RB_DIS_OP_MD); + + for (i = 0; i < 0xffff; ...

[www.kernel.org/pub/linux/kernel/people/akpm/patches/2.6/2.6.14-rc1/2.6.14-rc1-
 mm1/broken.../git-netdev-all.patch](http://www.kernel.org/pub/linux/kernel/people/akpm/patches/2.6/2.6.14-rc1/2.6.14-rc1-mm1/broken.../git-netdev-all.patch) - 234k - Cached - Similar pages

[PDF] MPC8540 PowerQUICC III™ Integrated Host Processor Reference Manual

File Format: PDF/Adobe Acrobat

Out-of-Sequence Tx Data Buffer Pointer Register (OSTBDP)..... 14-40

Doorbell Queue Enqueue Pointer Address Register (DQEPAR)

www.freescale.com/files/32bit/doc/ref_manual/MPC8540RM.pdf - Similar pages

[PPT] [Efficient User-Level Networking in Java](#)

File Format: Microsoft Powerpoint - [View as HTML](#)

`send/recv ticket ring, send/recv. queue. descriptor. buffer public ViIbufTicket register(Vi
vi); /* reg + pin jbuf */ ...`

[www.cs.cornell.edu/info/People/chichao/talk-final.ppt](#) - Similar pages

[\(WO/2004/093378\) AN APPARATUS AND METHOD FOR ALLOCATING RESOURCES...](#)

Although described as a "register," the data to be stored in doorbell register 620 As illustrated, a set of output queues 860 may temporarily buffer the ...

[www.wipo.int/pctdb/en/wo.jsp?WO=2004093378&IA=US2004010912&DISPLAY=DESC](#) - 143k - [Cached](#) - [Similar pages](#)

1 2 3 4 5 6 7 8 9 10 [Next](#)

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#) |
[Try Google Experimental](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Privacy](#) - [About Google](#)